

# KF-613 KoolFlex WalkGuard Safety Coating



## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 2024-08-16  
Revision date: 2024-08-16  
Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form	Mixture
Product name	KoolFlex WalkGuard Safety Coating
Product code	KF-613

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture	: Roof restoration and repair
Restrictions on use	: Industrial use

#### 1.3. Supplier

**Supplier**  
Kool Coats  
9975 High Country Lane  
Forney, TX 75126  
877-397-1496  
www.koolcoats.com

#### 1.4. Emergency telephone number

Emergency number	: CHEMTREC 1-800-424-9300
------------------	---------------------------

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Flammable liquid - Category 4; Carcinogenicity - Category 2

#### 2.2. GHS Label elements, including precautionary statements

##### GHS labelling

Hazard pictograms (GHS)



Signal word (GHS)

: Warning

Hazard statements (GHS)

: Combustible liquid.  
Suspected of causing cancer.

Precautionary statements (GHS)

: Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.  
Response:  
If exposed or concerned: Get medical advice or attention.  
Storage:  
Store in a well-ventilated place. Keep cool. Disposal:  
Dispose of contents and container in accordance with local, regional, national and international regulations.

# KF-613 KoolFlex WalkGuard Safety Coating

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015



### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	%
Siloxanes and Silicones di-Me, hydroxy-terminated	70131-67-8	40-60
silica	T.S.	30-40
Titanium dioxide	13463-67-7	5 -10
Polydimethylsiloxane	31692-79-2	1 - 5
2-Butanone, 0,0',0"- (methylsilyldyne)trioxime	22984-54-9	1 - 5
1-Propanamine, 3-(trimethoxysilyl)-	13822-56-5	0.1 - 1

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### 4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

# KF-613 KoolFlex WalkGuard Safety Coating

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015



### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

Unsuitable extinguishing media : Do not use water jet.

#### 5.2. Specific hazards arising from the chemical

Fire hazard : Not known to generate any hazardous decomposition products in a fire.

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

##### 6.1.1. For non-emergency personnel

No additional information available

##### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.

Hygiene measures : Take off contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Keep in a dry, cool and well-ventilated place. Do not expose to temperatures exceeding 50 °C/122 °F. Keep out of the reach of children.

# KF-613 KoolFlex WalkGuard Safety Coating

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015



### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

KoolFlex WalkGuard Safety Coating	
No additional information available	
Titanium Dioxide (13463-67-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Titanium dioxide
ACGIH OEL TWA	0.2 mg/m <sup>3</sup> (nanoscale respirable particulate matter) 2.5 mg/m <sup>3</sup> (finescale respirable particulate matter)
Remark (ACGIH)	TLV® Basis: LRT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Titanium dioxide (Total dust)
OSHA PEL TWA	15 mg/m <sup>3</sup> (total dust)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	5000 mg/m <sup>3</sup>
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	2.4 mg/m <sup>3</sup> (CIB 63-fine) 0.3 mg/m <sup>3</sup> (CIB 63-ultrafine, including engineered nanoscale)

#### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

#### 8.3. Individual protection measures/Personal protective equipment

<b>Hand protection:</b>
Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.
<b>Eye protection:</b>
Safety glasses or goggles are recommended when using product.
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

#### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

# KF-613 KoolFlex WalkGuard Safety Coating

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015



### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous.
Colour	: White
Flash point	: > 178 °F (>81 ° C)
Relative density	: ~1.3
Density	: 8.245 lb/gal (ASTM D-1475)
Solubility	: Insoluble in water
Viscosity, kinematic	: 12000 – 18000 centistokes

#### 9.2. Other information

VOC content	: <50 g/l
-------------	-----------

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Heat. Freezing. Incompatible materials.

#### 10.5. Incompatible materials

Strong oxidizers. Strong acids.

#### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Oxides of Silicone.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

#### 2-Butanone, 0,0',0''-(methylsilylidyne)trioxime

LD50 oral rat	Not available
LD50 dermal rat	2463 mg/kg bodyweight
ATE CA (oral)	Not available

#### 1-Propanamine, 3- (trimethoxysilyl)-

LD50 oral rat	7640 mg/kg
---------------	------------

# KF-613 KoolFlex WalkGuard Safety Coating

## Safety Data Sheet



According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 1-Propanamine, 3- (trimethoxysilyl)-

LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
LC50 inhalation rat	64000 ppm (4-hour exposure)
ATE CA (oral)	6450 mg/kg bodyweight

### Titanium Dioxide (13463-67-7)

LD50 oral rat	> 10000 mg/kg (Source: IUCLID)
LC50 inhalation rat	5.09 mg/l/4h
ATE CA (vapours)	5.09 mg/l/4h
ATE CA (dust,mist)	5.09 mg/l/4h

Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Not classified.
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.

### Titanium Dioxide (13463-67-7)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity : Not classified.  
Aspiration hazard : Not classified.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Not harmful to aquatic life, conclusion by analogy.

### Titanium Dioxide (13463-67-7)

LC50 - Fish [1]	155 mg/l Test organisms (species): other:Japanese Medaka
EC50 - Crustacea [1]	19.3 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 - Crustacea [2]	27.8 mg/l Test organisms (species): Daphnia magna
LOEC (chronic)	5 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	≥ 2.92 mg/l Test organisms (species): Daphnia magna Duration: '21 d'

### 12.2. Persistence and degradability

#### KoolFlex WalkGuard Safety Coating

Persistence and degradability : Not established.

### 12.3. Bioaccumulative potential

#### KoolFlex WalkGuard Safety Coating

Bioaccumulative potential : Not established.

### 12.4. Mobility in soil

No additional information available

# KF-613 KoolFlex WalkGuard Safety Coating

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015



### 12.5. Other adverse effects

Other information : No other effects known.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

## SECTION 14: Transport information

In accordance with DOT / TDG

### 14.1. UN number

UN-No.(DOT) : Not applicable  
UN-No. (TDG) : Not applicable

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable  
Proper Shipping Name (TDG) : Not applicable

### 14.3. Transport hazard class(es)

**DOT**  
Transport hazard class(es) (DOT) : Not applicable

**TDG**  
Transport hazard class(es) (TDG) : Not applicable

### 14.4. Packing group

Packing group (DOT) : Not applicable  
Packing group (TDG) : Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1 Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

# KF-613 KoolFlex WalkGuard Safety Coating

## Safety Data Sheet



According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

### 15.2. International regulations

No additional information available

### SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Revision date : 08/16/2024

Other information : None.

#### Full text of hazard classes and H-statements

Skin Sens. 1	Skin sensitisation, Category 1
--------------	--------------------------------

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.