



**KWIKSHOT TS-410 RUBBER PREP & COAT WATERPROOFING (TROWEL)**

**Basic Uses & Description:**

**TS-410 KwikShot Rubber Prep & Coat Waterproofing (Trowel-Grade)** is a thick, blue rubber seam filler for precision patching where spray isn't practical. Ideal for sealing joints, cracks, valleys, vents, and seams up to 5/8" wide. Delivers 200% elongation and 100% waterproofing at 30 mils while delivering durability with 200 psi tensile strength. Flexible, fabric-free, and built for long-lasting protection in detail areas.

**Precision Crack Sealing:**

Designed for joints, seams, and holes up to 5/8", offering detail-level waterproofing.

**No-Fabric Application:**

Creates a fully waterproof seal at 30 mils without reinforcement fabric, simplifying repairs.

**Application:**

**DO NOT MIX. DO NOT THIN.**

**SURFACE PREP:**

All surfaces must be sound and free of frost, dirt, grease, oil, loose nails & screws, sharp protrusions, or other contaminants that will hinder the adhesion of the membrane installation. Clean loose dust and dirt from the surface by brushing or wiping with a clean, dry cloth brush or broom.

**APPLICATION:**

Review product Application Guide before proceeding. Conduct a test patch to ensure proper adhesion.

- Dip edge of trowel into the Kwikshot™ Trowel Grade material and fill crack in one motion for shallow cracks and holes leaving material overlapping at approximately 1 inch
- Using the edge of the trowel slice down across the crack to remove excess material
- For deeper holes and cracks work trowel grade material down into crack using rectangular trowel, putty knife, or handheld scraper.
- Kwikshot™ Trowel Grade is dry when it turns deep dark blue with no visible light blue color
- Compatible with bulk loading caulk guns

**APPLICATION RECOMMENDATIONS:**

Apply between 50° - 90° F on a warm dry surface. Surface temperature must be 5° F higher than the dew point and rising.

- Do not allow product in packaging to freeze
- Do not apply in inclement weather and rain
- Do not apply if temperature is expected to drop below 32°F in the next 24 hours
- Do not install in area expected to reach 180°F or above
- Avoid direct exposure to sunlight for long periods of time.

<b>VOLUME SOLIDS</b>	59%
<b>WEIGHT PER GALLON</b>	ASTM D1475 12.36 lbs/gal
<b>COLOR</b>	Blue
<b>COVERAGE</b>	Dependent on application
<b>DRY TIME</b>	Allow 24 hours between coats
<b>CURE TIME</b>	7-10 days
<b>ELONGATION</b>	ASTM D2370 up to 200% at 20 mils DFT
<b>FINISH</b>	Flat - Paintable
<b>FLASH POINT</b>	>200° F
<b>HUMIDITY</b>	Best applied at 50% humidity or below
<b>MOLD &amp; MILDEW RESISTANCE</b>	No Growth
<b>PH AS SHIPPED</b>	ASTM E70 8.50-9.0
<b>TENSILE STRENGTH</b>	ASTM D2370 up to 200 psi at 20 mils DFT
<b>SHELF LIFE</b>	24 Months Unopened
<b>WATER SWELL</b>	ASTM 471D 4.22%
<b>V.O.C CONTENT</b>	< 50 g/l
<b>VAPOR PERMEABILITY</b>	0.156 Perms
<b>VISCOSITY</b>	200,000 CPS #7 @10

**Compliance**

<b>SCAQMD</b>	Yes
---------------	-----

**Handling & Storage:**

Clean up application equipment, tools, spills, hands immediately after use with water. Store unused product in the original container tightly sealed.

Dispose of product in accordance with local, state or federal requirements.





**KWIKSHOT TS-410 RUBBER PREP & COAT WATERPROOFING (TROWEL)**

**Safety:**

Do not take internally. Keep out of reach of children. Avoid contact with skin and eyes. Use hand and eye protection when using this product. Wash with soap and water after contact with skin. If eye-contact occurs rinse with clean water and seek medical advice if symptoms continue.

**Packaging Sizes:**

**TS-410 KwikShot Rubber Trowel Grade** is available in 5 & 1 gallon containers.

**Maintenance:**

The life of the roof may be extended by regularly scheduled maintenance. A roof should typically be inspected at least twice a year. The roof immediately needs to be inspected following severe weather and extraordinary maintenance on roof-mounted equipment.

**Limited Warranty Information:**

Kool Coats offers a 10-20 year Material Warranty. A 10-20 Year Labor and Material Warranty is available for a fee. For warranty details contact your Kool Coats representative.

**WARRANTY DISCLAIMER:**

This product is warranted solely to the original purchaser. This warranty is non-transferable and shall not apply to any subsequent resale or transfer of the product. To obtain warranty service, the original purchaser must provide valid proof of purchase. Kool Coats makes no warranties, expressed or implied, beyond those stated herein and reserves the right to modify these terms at any time without notice.