



**Basic Uses & Description:**

**RP-100 ProWash** is a concentrated, water-based roof cleaner formulated to remove dirt, debris, mildew, grease, and surface contaminants from roofing substrates prior to coating. Safe for use on metal, single-ply membranes (TPO, PVC, EPDM), modified bitumen, and more. ProWash is ideal for preparing surfaces to maximize coating adhesion and long-term performance.

**Instructions:**

HOW TO USE :

- Recommended to put in a pressure washer suction tube or dilute 5:1
- Allow to dwell 10–15 minutes, then rinse thoroughly with water
- Do not allow to dry on the surface
- Repeat as necessary for heavy buildup

**Storage & Handling:**

Store between 40°F and 90°F. Protect from freezing. Shelf life: 12 months in original, unopened container. Do not apply if surface temperature is below 50°F. Avoid use when rain or freezing conditions are expected within 24 hours. Not a substitute for adhesion primer. Avoid contact with eyes; wear gloves and eye protection.

**Packaging Sizes:**

**ProWash** is available in 5 gallon containers.

TEST PROPERTY	TEST VALUE
Appearance	Amber
Scent	Detergent/Soap
Weight per Gallon	8.36 lbs/gal
VOC Content	<50 g/L
Application Temp	40° F - 120° F
pH	10