



Basic Uses & Description:

RP-105 Rinseable EPDM Cleaner is a water based, zero VOC, single-component, high performance wash primer intended for use on EPDM surfaces. It is designed for application over aged EPDM surfaces, and can be applied with spray, brush, or roller. This is a wash primer, and is designed to be applied and washed off the roof shortly after.

Features:

- Zero-VOC, water-based wash primer designed specifically for aged EPDM membranes.
- Prepares surfaces for coating by cleaning and slightly etching the surface to ensure maximum adhesion.
- Applied and rinsed off shortly after, leaving a ready-to-coat surface without residue.

Application:

RP-105 Rinseable EPDM Cleaner is intended to be spray-applied. It can also be applied with a brush or roller. Surface should be clean and dry prior to application.

It should be applied at a rate of 1 gallon per 500 square feet. Allow cleaner to sit for 10-15 minutes on roof, then powerwash roof surface. If roof is not sufficiently cleaned for proper coating adhesion, repeat this process. Contact Kool Coats for equipment details for spray, roller, and brush applications.

Packaging Sizes:

RP-105 Rinseable EPDM Cleaner is available in 5 and 55 gallon containers.

TEST PROPERTY	TEST VALUE
Appearance	Clear
Total Solids Volume	64% ± 2%
Weight per Gallon	10 lbs/gal
VOC Content	<50 g/L
Clean Up	Water
Shelf Life	12 months

Storage & Handling:

This is a water based primer and is not freeze-thaw stable. It should be stored between 40°F and 70°F. Shelf life in unopened containers is 12 months from the manufacture date.

This product cures only by water evaporation. It should not be applied when the ambient temperature is below 50°F, or if there is a possibility the temperature could fall below 32°F within 24 hours.

Application is not recommended if rain or dew is expected before product dries.